

Gas Vent Pumping Packer

Liner Hangers & Accessories

The Gas Vent Pumping Packer is a simple, inexpensive method to isolate casing leaks or non-productive perforations in a rod pumping production installation. The interval between cups is adjustable to any length.

Features

- Inexpensive method to isolate casing leaks
- Interval between cups adjustable to any length
- Capable of venting gas to surface past insulated zone

Applications

Isolate casing leaks or nonproductive perforations in a rod pumping production installation. The Gas Vent Packer will allow the capability for venting gas to the surface past the isolated zone preventing gas locking of the pump.

Gas Vent Pumping Packer									
Size		O.D.		I.D.		Packer			
						Maximum O.D.*		Minimum O.D.*	
in	mm	in	mm	in	mm	in	mm	in	mm
4-1/2	114.3	2.375	60.33	3.00	76.20	3.750	95.25	2.687	68.25
5-1/2	139.70	2.375	60.33	3.00	76.20	4.625	117.48	2.750	69.85
5-1/2	139.70	2.875	73.03	4.00	101.60	4.625	117.48	3.188	80.98
7	177.80	2.375	60.33	4.00	101.60	5.000	127.00	2.750	69.85
7	177.80	2.875	73.03	4.50	114.30	5.000	127.00	3.188	80.98

