

XT-2 Service Packer

Service Equipment

The XT-2 Service Packer is a quarter-turn, compression set, retrievable packer that is capable of holding high pressure from above and below. It is used for acidizing, fracturing, cementing, and casing pressure tests.

Features

- Full opening packer bore
- Hydraulic hold down pistons for pressure from below
- Built in unloader system
- Large by-pass area
- Left-hand manual J is standard
- Other J systems are available
- Internal latch mechanism allows circulation at high rates of speed

XT-2 Service Packer						
Casing				Packer		Thread Connection
Size in	Weight Range lb/ft	Min in	Max in	Size	Max O.D. in	
4-1/2	9.5 – 13.5	3.920	4.090	43A	3.75	2.375 EU 8RD
5	15 – 18	4.408	4.276	43B	4.110	
5-1/2	20 – 23	4.670	4.778	45A2	4.500	
	15.5 – 20	4.778	4.892	45A4	4.640	
	13 – 15.5	4.892	5.044	45B	4.760	2.875 EU 8RD
7	32 – 35	6.004	6.094	47A4	5.812	
	26 – 29	6.094	6.276	47B2	5.950	
	20 – 26	6.276	6.538	47B4	6.078	
7-5/8	33.7 – 39	6.625	6.765	47C4	6.453	2.875 EU 8RD
	26.4 – 33.7	6.765	6.969	47C6	6.593	
	24 – 29.7	6.875	7.025	47D2	6.672	
	20 – 24	7.025	7.125	47D4	6.812	
mm	kg/ft	mm	mm	Size	mm	
114.3	14.14 – 20.09	99.57	103.89	43A	95.25	66.33 EU 8RD
127	22.32 – 26.78	111.96	108.61	43B	104.39	
139.7	29.76 – 34.22	118.62	121.36	45A2	114.30	
	23.06 – 29.76	121.36	124.26	45A4	117.86	
	19.34 – 23.06	124.26	128.12	45B	120.90	73.03 EU 8RD
177.8	47.62 – 52.08	152.50	154.79	47A4	147.62	
	38.69 – 43.15	154.79	159.41	47B2	151.43	
	29.76 – 38.69	159.41	166.07	47B4	154.38	
193.68	50.15 – 58.03	168.28	171.83	47C4	163.91	
	39.28 – 50.15	171.83	177.01	47C6	167.46	
	35.71 – 44.19	174.63	178.44	47D2	169.47	
	29.76 – 35.71	178.44	180.98	47D4	173.02	

