

Retrievable Inflatable Bridge Plugs are wellbore isolation tools designed for cased or open hole applications, including remedial treatment, water shut-off, and a host of other zone isolation tasks. Inflatable packers are designed so that they may be run through wellbore restrictions and set in less than ideal well conditions.

Features

- Small run-in O.D. to pass through wellbore restrictions
- Large inflation capacity
- Run-in O.D. from 3.5 to 15 inches (88.9 mm to 381 mm)
- Differential pressures to 5,500 psi (38 mPa)
- Available for sour service
- Set with pump pressure only
- Left-hand or right-hand off or straight shear
- Designed for cased or open hole
- Run on tubing, coiled tubing, or drill pipe

Retrievable Inflatable Bridge Plug							
Run-In O.D.		Maximum Inflated O.D.		Mandrel I.D.		Connection	
in	mm	in	mm	in	mm	in	mm
3-1/2	88.9	7	177.8	1.250	31.7	2.375	60.3
3-7/8	98.4	7-3/4	196.9	1.250	31.7	2.375	60.3
4-1/4	108.0	8-1/2	215.9	2.000	50.8	2.375	60.3
4-5/8	117.5	9-1/4	235.0	2.000	50.8	2.375	60.3
5-1/2	139.7	11	279.4	2.000	50.8	2.375	60.3
6-1/4	158.8	12-1/2	317.5	2.000	50.8	2.375	60.3
6-3/4	171.5	13-1/2	342.9	2.000	50.8	2.375	60.3
5-1/2	139.7	11	279.4	2.500	63.5	2.875	73.0
6-1/4	158.5	12-1/2	317.5	2.500	63.5	2.875	73.0
6-3/4	171.5	13-1/2	342.9	2.500	63.5	2.875	73.0
7-1/2	190.5	15	381.0	2.500	63.5	2.875	73.0
9-1/4	235.0	18-1/2	469.9	2.500	63.5	2.875	73.0
10-1/2	266.7	21	533.4	2.500	63.5	2.875	73.0
11	279.4	22	558.8	2.500	63.5	2.875	73.0
15	381.0	30	762.0	2.500	63.5	2.875	73.0

Other sizes available upon request.

