



The SCX is a tubing profile nipple designed for use with top no-go or selective wireline flow control equipment. The SCX nipple contains a close tolerance polished seal surface, a locking groove, and a top no-go shoulder. The top no-go shoulder and groove are utilized for the location and installation of top no-go devices, and the locking groove to locate and lock selective locks. As standard, all profile nipples are manufactured from high quality alloy steels that meet NACE MR-01-75 (latest edition) specifications. SCX profile nipples are also available in other materials for high corrosion applications and are also available with anticorrosion coatings and hard coat- ings. SCX profile nipples are available with API connections (including EUE with seals) or with most premium tubing connections. Every SCX nipple is individually checked to ensure each and every nipple meets high quality standards. When designing a completion, the location and size of the profile nipples must receive careful consideration to assure that the versatility and functionality of the completion design are maximized.

Features

- **Integral one-piece design with polished close tolerance seal bore and locking groove**
- **Accepts a wide variety of readily available locks and accessory equipment**
- **Available in a wide variety of materials, coatings, and threads**

Applications

For the installation of:

- **Blanking plugs to shut off or isolate flow with in a well**
- **Bottom hole chokes, Check valves and Instruments**
- **Other specialized flow control equipment**

SCX Profile Nipple					
Nominal Tubing Size		Seal Bore I.D.		Standard O.D.	
in	mm	in	mm	in	mm
1.9	48.3	1.500	38.1	2.13	54.1
2-1/16	52.4	1.625	41.3	2.34	59.4
2-3/8	60.3	1.875	47.6	2.71	68.8
2-7/8	73.0	2.313	58.8	3.23	82.0
3-1/2	88.9	2.750	69.9	4.25	108.0