



The SCXN is a tubing profile nipple designed for use with bottom no-go flow control equipment. The SCXN Profile Nipple contains a close tolerance polished seal surface, a locking groove and a bottom no-go shoulder. The bottom no-go shoulder is utilized for the location and installation of bottom no-go locks. As standard, all profile nipples are manufactured from high quality alloy steels that meet NACE MR-01-75 (latest edition) specifications. SCXN Profile Nipples are also available in other materials for high corrosion applications and are also available with anticorrosion coatings and hard coatings. SCXN profile nipples are available with API connections (including EUE with seals) or with most premium tubing connections. Every SCXN Profile Nipple is individually checked to ensure each and every nipple meets high quality standards. When designing a completion, the location and size of the profile nipples must receive careful consideration to assure that the versatility and functionality of the completion design are maximized. The SCXN is generally used as the only profile nipple at the bottom most nipple in the tubing string.

Features

- **Integral one-piece design with polished close tolerance seal bore no-go ring and locking groove**
- **Accepts readily available locks and accessory equipment**
- **Available in a wide variety of materials, coatings, and threads**

Applications

For the installation of:

- **Blanking plugs to shut off or isolate flow with in a well**
- **Bottom hole chokes, Check valves and Instruments**
- **Other specialized flow control equipment**

SCXN Profile Nipple							
Nominal Tubing Size		Seal Bore I.D.		No-Go I.D.		Standard O.D.	
in	mm	in	mm	in	mm	in	mm
1.9	48.3	1.500	38.1	1.448	36.8	2.13	54.1
2-1/16	52.4	1.625	41.3	1.536	39.0	2.34	59.4
2-3/8	60.3	1.875	47.6	1.791	45.5	2.71	68.8
2-7/8	73.0	2.313	58.8	2.205	56.0	3.23	82.0
3-1/2	88.9	2.750	69.9	2.635	66.9	4.25	108.0